

Chain Block

- High quality bearings on side plates, gearbox and load chain sheave ensure smooth operation of load chain and drive pinion. Optimized hand forces set standards for easy operation.
- Strong bolts between side plates and housing cover and the reinforced hand wheel cover ensure increased stability.
- Precision machined guide rollers ensure smooth running of the load chain.
- High quality bearings for gearbox, side plates and load chain sheave permit a long service life.
- Zinc-plated and yellow-chromate brake parts and guide rollers ensure increased corrosion protection.
- Premium Grade Alloy Zinc-plated load chain as standard for added corrosion protection.
- Automatic Double Pawl Breaking System.
- Drop Forged and Special Heat Treated Hooks for Great Strength.



CODE	Capacity Ton	Pull Rated Load (N)	Lift m	Load Chain Size	No. of Falls	Weight Kg
WA-CH005300	0.5	221	3	6x18	1	8.5
WA-CH005500	0.5	221	5	6x18	1	11.9
WA-CH010300	1.0	304	3	6x18	1	10.5
WA-CH010500	1.0	304	5	6x18	1	13.9
WA-CH015300	1.5	343	3	6x18	1	16.5
WA-CH015500	1.5	343	5	6x18	1	21.1
WA-CH020300	2.0	457	3	8x24	1	16.8
WA-CH020500	2.0	456	5	8x24	1	21.4
WA-CH030300	3.0	390	3	8x24	2	24.0
WA-CH030500	3.0	390	5	8x24	2	31.4
WA-CH050300	5.0	420	3	10x30	2	40.0
WA-CH050500	5.0	420	5	10x30	2	50.6
WA-CH100300	10.0	392	3	10x30	4	74.0
WA-CH100500	10.0	392	5	10x30	4	93.4

* Load Chain Length can be custom order.

Lever Block

- Due to optimized gearing and improved bearings in the housing cover a minimum effort is required to operate the short hand lever.
- Steel hand wheel as standard.
- Automatic screw-and-disc type load brake with corrosion protected components.
- Standard free chaining device to quickly attach the load or to pull the chain through the hoist in both directions.
- Robust chain guide rollers eliminate fouling and jamming of chain on the load sheave.
- Sturdy bottom block with encapsulated bolt connections
- Alloyed steel link chain with zinc-plated yellow chromate finish, in accordance with national and international standards and regulations.
- Drop forged suspension and load hooks are made from non-aging, high tensile steel and fitted with robust safety latches.



CODE	Capacity Ton	Pull Rated Load (N)	Std Lift m	Load Chain	No. of Falls	Weight Kg
WA-LH0750	0.75	140	1.5	6x18	1	6.4
WA-LH1500	1.50	220	1.5	8x24	1	11.3
WA-LH3000	3.00	320	1.5	10x30	1	19.3
WA-LH6000	6.00	340	1.5	10x30	2	31.3

* Load Chain Length can be custom order.

FATOOLS®

Plain Trolley

- It has excellent rolling features due to machined steel wheels mounted on prelubricated, encapsulated ball bearings.
- Adjustable to fit a wide range of beam widths and profiles (e.g. INP, IPE and IPB).
- Adjustments are made by rotating the clevis load bar which also ensures the centered positioning of the hoist in the clevis – no creeping to the left or the right.
- Test Load 150%



CODE	Capacity Ton	I-Beam Width	Min Radius curve (m)	Weight Kg	Std Pack
WA-PT0500	0.5	50-152	1	7.1	1
WA-PT1000	1.0	64-203	1	12.8	1
WA-PT2000	2.0	88-203	1.1	18.8	1
WA-PT3000	3.0	100-203	1.3	33.7	1
WA-PT5000	5.0	114-203	1.4	50.7	1

Geared Trolley

- It has excellent rolling features due to machined steel wheels mounted on prelubricated, encapsulated ball bearings.
- Adjustable to fit a wide range of beam widths and profiles (e.g. INP, IPE and IPB).
- Adjustments are made by rotating the clevis load bar which also ensures the centered positioning of the hoist in the clevis – no creeping to the left or the right.
- Test Load 150%



CODE	Capacity Ton	I-Beam Width	Min Radius curve (m)	Weight Kg	Std Pack
WA-GT0500	0.5	50-152	1	12.0	1
WA-GT1000	1.0	64-203	1	17.0	1
WA-GT2000	2.0	88-203	1.1	23.5	1
WA-GT3000	3.0	100-203	1.3	38.7	1
WA-GT5000	5.0	114-203	1.4	55.7	1

- They can be used to lift, pull and position loads over great distances depending on the wire rope length.
- Low weight—quick installation
- No limitation in terms of cable length
- Manageable, light-weight, robust, powerful
- Increase load capacity with deflection sheaves
- Overload protection
- Precise load placement within millimeters



CODE	Capacity Ton	Wire Rope dia. mm	Wire Rope Lg m	Wire Rope Break Strength kg	Machine Wt Kg	Wire Rope Wt Kg
WA-HP3200	3.2	16.3	20	16000	27	26.6

FATOOLS®

Webbing Sling 7:1

- Webbing Slings are lightweight lifting slings.
- WALES Duplex Polyester Webbing Slings are less likely to scratch or damage the load & have excellent elongation properties.
- A Webbing Sling is suitable for use in choker, vertical & basket hitches.
- Double folded eye loops on both ends.
- Reinforced two-ply polyester construction.
- Triple stitched throughout.
- According to 98/37/EC Directives.
- Color coded according to EN1492-1.
- Safety factor 7:1



CODE	Color	SWL Ton	Width In	Total Length m
WA-WS010200	Violet	1	1	2
WA-WS010300	Violet	1	1	3
WA-WS010400	Violet	1	1	4
WA-WS010600	Violet	1	1	6
WA-WS020200	Green	2	2	2
WA-WS020300	Green	2	2	3
WA-WS020400	Green	2	2	4
WA-WS020600	Green	2	2	6
WA-WS030200	Yellow	3	3	2
WA-WS030300	Yellow	3	3	3
WA-WS030400	Yellow	3	3	4
WA-WS030600	Yellow	3	3	6
WA-WS040400	Grey	4	4	4
WA-WS040600	Grey	4	4	6
WA-WS050400	Red	5	5	4
WA-WS050600	Red	5	5	6
WA-WS050800	Red	5	5	8
WA-WS051000	Red	5	5	10

CODE	Color	SWL Ton	Width In	Total Length m
WA-WS060400	Brown	6	6	4
WA-WS060600	Brown	6	6	6
WA-WS080400	Blue	8	8	4
WA-WS080600	Blue	8	8	6
WA-WS080800	Blue	8	8	8
WA-WS081000	Blue	8	8	10
WA-WS100400	Orange	10	10	4
WA-WS100600	Orange	10	10	6
WA-WS100800	Orange	10	10	8
WA-WS101000	Orange	10	10	10
WA-WS120400	Orange	12	12	4
WA-WS120600	Orange	12	12	6

FATOOLS®

Ratchet Tie Down

- This Double J-Hook Ratchet Tie-Down is made of heavy-duty polypropylene webbing for large work loads.
- Rugged heavy-gauge steel ratchet is designed to withstand the rigors of heavy-duty cargo transport.
- Ratchet is constructed of rugged, heavy-gauge steel to secure your heavy loads.



CODE	Width In	Length m	Assembly Breaking Strength Kg	WLL Kg	Weight Lbs
WA-RD250300	1"	3	1,000	500	0,7
WA-RD250600	1"	6	1,000	500	0,8
WA-RD500600	2"	6	5,000	2,500	2,6
WA-RD501200	2"	12	5,000	2,500	3,2
WA-RD750600	3"	6	7.500	3,750	5,6
WA-RD751200	3"	12	7.500	3,750	6,6

FATOOLS®

Ratchet Puller Set

- Ratchet puller with grip



CODE	Capacity Ton	Wt Kg	Std Pack
22023-27	1.5	5.9	1

Ratchet Puller

- Ratchet puller.
- wire rope 6mm x 2200



CODE	Capacity Ton	Level Length	Min L mm	Max L mm	Wt Kg	Std Pack
22023-07	1.5	430	450	1250	4.5	1

Grip

- Grip for wire rope, messenger wire, copper cable, trolley cable.
- Safety load 20KN or 2 Ton
- Min wire dia. 5mm
- Max wire dia. 16mm



CODE	Capacity Ton	Wt Kg	Std Pack
22023-17	2.0	1.4	1

FATTOOLS®

Gator Drum Grip with 360kg Capacity, 55 Gallons Drum Lifter

- Specialized accessory of forklift for carrying and stacking drums
- Heavy duty design, delicate structure and simple operation
- Carry one drum by the automatic grip lock.
- Maintains positive grip over rough floor surface.
- Gator Grip lock will NOT open and ensures safe secure drum transport.
- Grip head is differently positioned to fit different height.
- Easily carry and have much more safety.



	Capacity	Fork Dimension		Weight	Std Pack
CODE	Kg	W	Hole	Kg	
WA-DG360A	360	560	65x180	60	1

Gator Drum Grip with 720kg Cap, 55 Gallons Drum Lifter

- Specialized accessory of forklift for carrying and stacking drums
- Heavy duty designs, delicate structure and simple operation.
- Carry Two drums by the automatic grip lock.
- Maintains positive grip over rough floor surface.
- Gator Grip lock will NOT open and ensures safe secure drum transport.
- Grip head is differently positioned to fit different height.
- Easily carry and have much more safety.



	Capacity	Fork Dimension		Weight	Std Pack
CODE	Kg	W	Hole	Kg	
WA-DG720A	720	605	65x180	96	1

Drum Lifter

- Specialized accessory for carrying and lifting drums.
- For lifting 210 litre open top and tight head steel drum, and plastic drums with L or X rings.
- Welded gripping hooks.
- Fitted with 20mm diameter steel pin for attaching to overhead hoist or crane.
- Heavy duty design, delicate structure and simple operation
- Specifications:
 - Capacity: 360kg
 - Suitable drum: 55 gallons
 - 3 legs



	Capacity	Weight	Std Pack
CODE	Kg	Kg	
WA-DL360	360	4.5	1

Drum Lifter

- Specialized accessory for carrying and lifting drums.
- For lifting 210 litre open top and tight head steel drum, and plastic drums with L or X rings.
- Welded gripping hooks.
- Fitted with 20mm diameter steel pin for attaching to overhead hoist or crane.
- Heavy duty design, delicate structure and simple operation
- Specifications:
 - Capacity: 360kg
 - Suitable drum: 55 gallons
 - 2 legs



	Capacity	Weight	Std Pack
CODE	Kg	Kg	
WA-DL350	360	9.5	1

Drum Lifter

- Specialized accessory for carrying and lifting drums.
- Semi-automatic tong model DN500 suitable for steel drums-open top and tight head.
- To operate set locking lever in locked open position.
- When central over the horizontal drum release lever to allow hooks to fall and locate under both rims. Hooks automatically engage as is lifted and disengage as drum is set down.



	Capacity	Weight	Std Pack
CODE	Kg	Kg	
WA-DN500	500	7.6	1

FATOOLS®

Telescopic Barrel Lifter

- Convert a forklift truck into a mobile crane to reach and transport long and awkward loads from inaccessible location.
- Verify load centre of forklift truck.
- Safety chain wed eel to boom has grab hooks for anchoring job boom to forklift truck.
- Zinc plated fork heels pin for safe forklift attachment.
- Specifications:
 - Capacity: 3000kg
 - Suitable fork size: 180 x 74mm
 - Net weight: 240 kg



	Capacity	Fork Dimension		Weight	Std Pack
CODE	Kg	W	Hole	Kg	
WA-TLB03	3000	560	65x180	60	1

FATOOLS®

Hand Pallet Truck

- Capacity 3000 kg
- For the professional transportation of palletized goods and box pallets under demanding conditions.
- Ergonomic safety control handle for one-hand operation of lifting, driving and lowering.
- Ergonomic designed control handle for safe handling.
- Low maintenance high performance hydraulic pump with hard chromium plated piston and pressure relief valve.
- Frame and forks in robust steel construction, adjustable connecting rods, especially hardened axles and the high quality powder coating ensure a long life expectancy.
- Steering angle of 105 degree to each side for easy handling in confined spaces.
- Entry rollers facilitate entry into bottom boarded pallets.



CODE	Capacity	Fork Dimension		Weight	Std Pack
	Ton	W	L	Kg	
WA-HT3000S	3.0				1
WA-HT3000	3.0				1

FATOOLS®